



DATA SHEET

residual current circuit-breaker

DFS 2 025-2/0,03-A Hz400

sensitive to pulsating and alternating currents Type A, for frequencies
 $\neq 50$ Hz

Article number 09124637



Function

Residual current circuit-breakers (RCCBs) are components for implementing protective measure "Automatic disconnection of the power supply" as per VDE 0100 part 410 or corresponding international installation regulations. Series DFS 2 devices are compact two-pole residual current circuit-breakers for single-phase networks. In the standard design, they only take up two module-width units of space. In spite of the compact dimensions, a number of different tripping currents and characteristics are available at rated currents, depending on the design, up to 125 A. They also have large two-tier terminals for large conductor cross-sections, a practical multi-functional switch toggle and can be provided with labels using free-of-charge software. Type A residual current circuit-breakers are sensitive to pulsating and alternating currents. This function is independent of the mains voltage. Devices in the Hz design are intended for rated mains frequencies other than 50 Hz. Common frequencies are 60 or 400 Hz; devices for other frequencies can be manufactured upon request. The frequency range for tripping current detection remains unaffected by this. Devices in the standard design are intended for monitoring circuits with a rated voltage of 230 V or 400 V.

Features

tripping not dependent on mains and auxiliary voltage, sensitive to AC residual currents and pulsating DC residual currents (type A), compact design for all rated currents, high short-circuit resistance, double-sided two-tier terminals for large conductor cross-section and busbar, switch position indicator, viewing window for labels, multifunction switch toggle with three positions: "on", "off" and "tripped", Neutral conductor position left or right

Mounting

quick fastening to mounting rail, any installation position, supply from any direction

Applications

Power supplies to TT, TN-S and TN-C-S networks with mains frequencies > 50 Hz, Not permitted for use in TN-C networks and for protecting systems in which electronic equipment may cause smooth DC residual currents or residual currents with frequencies not equal to 50 Hz. Comprehensive protection is not provided with an RCCB Type A. For these applications we recommend our residual current circuit-breakers Type F or our AC/DC sensitive residual current circuit-breakers Type B/B+.

Accessories

automatic reclosing devices DFA, terminal caps KA, information stickers HAS, auxiliary switches DHi, restart locks DFS WES, software DBS

Technical Data

| Technical Data | DFS 2 025-2/0,03-A Hz400 |
|--|--------------------------|
| Series | DFS 2 A Hz |
| Number of poles | 2 |
| Residual current type | A |
| Rated current (AC) | 25 A |
| Rated residual current $I_{\Delta n}$ | 0.03 A |
| Short-time delayed | false |
| Selective | false |
| min. Operating voltage range of test circuit | 150 V |
| max. Operating voltage range of test circuit | 250 V |

Subject to technical changes

| Technical Data | | DFS 2 025-2/0,03-A Hz400 |
|---|--|---|
| Maximum disconnection times | | $5 \cdot I\Delta n: \leq 40 \text{ ms}$ |
| | | load circuit |
| Specification | | load disconnect contact |
| min. Contact opening | | 4 mm |
| Rated voltage (AC) | | 230 V |
| Rated current (AC) | | 25 A |
| Rated short-circuit current | | 10 kA |
| Surge current strength | | 0.25 kA |
| max. Total rated switching capacity | | 500 A |
| Rated insulation voltage | | 400 V |
| Rated impulse withstand voltage | | 4 kV |
| Rated frequency | | 150 Hz ... 400 Hz |
| Current heat loss per current path | | 0.5 W |
| Thermal Backup-fuse OCPD | | 25 A |
| Short-circuit backup-fuse SCPD | | 100 A |
| Back-up fuse type | | gG |
| | | screw-type terminal top and bottom (load circuit) |
| Neutral conductor position | | left or right |
| Protection against direct contact | | DGUV V3, VDE 0660-514, finger and back-of-hand proof |
| Connection C1 Maximum number of conductors per terminal | | 2 (conductors of same type and cross-section) |
| Cross section solid | | 1-wire: 1.5 mm ² ... 50 mm ² ; 2-wire: 1.5 mm ² ... 16 mm ² |
| Connecting capacity flexible | | 1-wire: 1.5 mm ² ... 50 mm ² ; 2-wire: 1.5 mm ² ... 16 mm ² |
| Cross section stranded | | 1-wire: 1.5 mm ² ... 50 mm ² ; 2-wire: 1.5 mm ² ... 16 mm ² |
| Cross section AWG, solid | | 15 ... 1 |
| Cross section AWG, stranded | | 15 ... 1 |
| Cross section AWG, flexible | | 15 ... 1 |
| Cross section AWG, flexible with ferrule | | 15 ... 1 |
| Tightening torque | | 2.5 Nm ... 3 Nm |
| | | General data |
| Operating position | | optional |
| max. Operating altitude above MSL | | 2000 m |
| Mechanical endurance | | min. 5000 cycles |
| Electrical endurance | | min. 2000 cycles |
| Surrounding atmosphere | | normal environmental conditions |
| Storage temperature | | -35 °C ... 75 °C |
| Ambient temperature | | -25 °C ... 40 °C |
| Climate resistance | | according to IEC 60068-2-30: humid heat / cyclic (25 °C / 55 °C; 93 % / 97 % RH) |
| Shock resistance | | 20 g / 20 ms Duration |
| Fatigue limit | | > 5 g (f ≤ 80 Hz, duration > 30 min.) |
| Housing type | | distribution board housing |
| Installation type | | Mounting rail (35 mm) |
| Housing material | | thermoplastic |
| Protection class | | IP20 (installed: IP40) |
| sealable | | true |
| Width | | 36 mm |

Subject to technical changes

| Technical Data | DFS 2 025-2/0,03-A Hz400 |
|-------------------------------|-----------------------------|
| Height | 85 mm |
| Depth | 75 mm |
| Installation depth | 69 mm |
| Module widths | 2 |
| Weight | 0.264 kg |
| Design requirements/Standards | VDE 0664-10, DIN EN 61008-1 |
| Degree of pollution | 2 |

Dimensions



Dimensional drawing Group view

Wiring example



Wiring diagram