

DATA SHEET

Article number: 09914081

miniature circuit-breakers DLS 6h B10-2

for commercial sector applications, B-characteristic, 6 kA



6000 🕸

Function

The task of miniature circuit breakers is to automatically disconnect circuits in order to protect lines and connected devices. After disconnection, they can be manually reactivated without the fuse sets having to be replaced, for example. Each of our miniature circuit breakers is equipped with a trip-free mechanism, which guarantees safe deactivation even if, for example, a switching knob is mechanically blocked. A key requirement in DIN VDE 0100 is to protect cables, lines and installation devices from overload and shortcircuit. This can be achieved using miniature circuit-breaker (MCBs). In industrial installations and also in commercial buildings, they often take on additional protection of equipment and devices where there are usually stricter requirements than when used in residential buildings. Miniature circuit-breakers utilise both the magnetic and heat effect of the electrical current. If the current jumps to a value that is too high when a short-circuit occurs, the MCB interrupts the circuit using the magnetic field of an energised coil. The heat that develops when there is continuous overload causes the bimetal to warp, which trips the breaker. The DLS 6 family of miniature circuit-breakers, characterised by a large selection of different types for broad application fields, are available for residential and purpose-built facilities, as well as for industrial applications. The compact design provides lots of space for wiring and large clamping area, as well as the option of using conventional wiring rails for easy processing. The variants also have a large, folding label window and a clearly labelled display for the operating status. A number of additional devices such as under-voltage and operating current trip, and auxiliary/fault sensor switches, render possible general-purpose use of the miniature circuit-breakers. The DLS 6h variant for skilled trade features a rated switching capacity of 6 kA designed for distributor and final circuits, and a large selection of rated currents in characteristics B and C. Switches with tripping characteristic B ensure the standard protection for lighting and socket circuits.

Features

rated switching capacity 6 kA, screw terminals with strain-relief clamps with wide terminal cross-section range for rail and line wiring on both connection sides, special quick fastening for removal of multiple miniature circuit-breakers from the bottom or top interconnection, large, folding label window for a secure hold and protection of the label, use of conventional wiring rails, ON/OFF switch position indicator on the switch toggle, accessories retro-fittable on the right, labelling software free of charge

Mounting

quick fastening to mounting rail, any installation position

Applications

suitable for use in power supplies for residential and purpose-built buildings or buildings for commercial use

Accessories

terminal caps KA, software DBS, restart locks DEASS, auxiliary switches DHi, trip-indicating auxiliary contact DHi-S, operating current trip DASA, documentation

Technical data


Series	DLS 6h
Number of poles	2
Tripping characteristic	В
Supply side	left or right
Adjustment range of overload tripping	1.13 1.45
Adjustment range of short-circuit tripping	3 5
Tripping factor over frequency band	1.5 at DC; 1.1 at 100 Hz; 1.2 at 200 Hz; 1.3 at 300 Hz; 1.4 at 400 Hz
Test current factor tripping electromagnetic	5
Test current multiplier, trip, thermal	1.45
Test current factor retaining electromagnetic	3
Test current factor retaining thermal	1.13
Reference temperature thermal release	30 °C
Isolation class	C at 250 V AC; B at 400 V AC
	load circuit

Technical changes reserved 2025_10_14 doepke_09914081_dbl_en.pdf 1/3

C ::::	
Specification	load disconnect contact
Rated voltage (AC)	230 V, 400 V
Rated voltage (DC)	125 V (for both poles connected in series)
Rated current (AC)	10 A
Rated current (DC)	10 A
Rated short-circuit current	6 kA
Rated insulation voltage	2 kV
Rated impulse withstand voltage	4 kV
Rated frequency	50 Hz (16.67 Hz 60 Hz)
Current heat loss per current path	1.3 W
Short-circuit backup-fuse SCPD	125 A
Back-up fuse type	gL, gG
Back-up fuse (textual)	Safety fuse as per DIN EN 0636
nax. I²t let-through value	35 kA²s
Overvoltage class	
3	screw terminals with strain-relief clamp top (load circuit)
Protection against direct contact	DGUV V2, VDE o660-514, finger and back-of-hand proof
Connection C1 Maximum number of	2 (conductors of same type and cross-section)
onductors per terminal	2 (conductors of sume type and cross section)
Cross section solid	1-wire: 0.5 mm ² 25 mm ²
Connecting capacity flexible	1-wire: 1 mm² 16 mm²
Cross section flexible with ferrule	0.5 mm ² 16 mm ²
ross section stranded	1-wire: 1.5 mm ² 25 mm ²
ightening torque	max. 2.5 Nm
hickness busbar	max. 3 mm
hickness busbar cable lug (combined	2 mm
onductors, max)	
Cross section (busbar / busbar fork combined, nax)	25 mm²
,	screw terminals with strain-relief clamp bottom (load circuit)
Protection against direct contact	DGUV V2, VDE o660-514, finger and back-of-hand proof
Connection C2 Maximum number of onductors per terminal	2 (conductors of same type and cross-section)
Cross section solid	1-wire: 0.5 mm ² 35 mm ²
Connecting capacity flexible	1-wire: 1 mm ² 25 mm ²
Cross section flexible with ferrule	0.5 mm ² 16 mm ²
Cross section riexible with refroite	<u>.</u>
	1-wire: 1.5 mm ² 35 mm ²
ightening torque	max. 2.5 Nm
hickness busbar cable lug (combined conductors, max)	2 mm
Cross section (busbar / busbar fork combined, max)	35 mm²
Thickness busbar	max. 3 mm
	General data
Operating position	optional
Mechanical endurance	min. 20000 switching cycles
torage temperature	-40 °C 70 °C
mbient temperature	-40 °C 70 °C 55 °C
•	
limate resistance	damp/heat: constant as per DIN EN 60068-2-78, cyclical as per DIN EN 60068-2-30
hock resistance	25 g / 11 ms Duration
ibration resistance	> 15 g acc. to DIN EN 60068-2-59 during a load with l1
lousing type	distribution board housing
nstallation type	Mounting rail (35 mm)
lousing material	thermoplastic
rotection class	IP ₂₀
ealable	true
Vidth	35.4 mm
leight	82.5 mm
Pepth	74 mm
nstallation depth	68 mm
Module widths	2
Veight	0.232 kg
Design requirements/Standards	EN 60898-1
•	•
Power limitation category	3

Degree of pollution

Dimensions




Dimensioned drawing miniature circuit-breakers DLS 6h B10-2

Wiring example



Wiring example miniature circuit-breakers DLS 6h B10-2

Diagrams



Diagrams miniature circuit-breakers DLS 6h B10-2

2