

DATA SHEET
Article number : 09915028

miniature circuit-breakers ELS 3 B4o/1+N

Compact design



1/2



Function

The task of miniature circuit breakers is to automatically disconnect circuits in order to protect lines and connected devices. After disconnection, they can be manually reactivated without the fuse sets having to be replaced, for example. Each of our miniature circuit breakers is equipped with a trip-free mechanism, which guarantees safe deactivation even if, for example, a switching knob is mechanically blocked. Miniature circuit-breakers from series ELS have a compact design. A guide phase and neutral conductor (1+N) are monitored at a width of only 1 TE. Furthermore, they feature a contact position indicator and protection against wires behind lodged behind terminals. They can be used for rated short-circuit currents up to 6 kA. Switches with tripping characteristic B ensure the standard protection for lighting and socket circuits.

Features

high-quality miniature circuit-breakers 1+N in 1 module width unit for space-saving installation, switching position indicator red/green, Protection against wires being lodged behind terminals, extensive range of accessories which can be retro-fitted, rated switching capacity 6 kA as per EN 60898

Mounting

quick fastening to mounting rail, any installation position

Applications

suitable for use in power supplies for industrial facilities and purpose-built buildings or buildings for commercial use

Accessories


auxiliary switches Hi, restart locks RH-SPE

Technical data

Series	ELS ₃
Number of poles	1+N
Tripping characteristic	В
	load circuit
Specification	load disconnect contact
Rated voltage (AC)	230 V
Rated current (AC)	40 A
Rated short-circuit current	6 kA
Rated frequency	50 Hz, 60 Hz
Current heat loss per current path	3.7 W
Overvoltage class	
-	screw-type terminal top and bottom (load circuit)
Connection C1 Maximum number of	(conductors of same type and cross-section)
conductors per terminal	
Cross section solid	1-wire: 1 mm ² 10 mm ²
Cross section stranded	1-wire: 1 mm ² 10 mm ²
Tightening torque	1.2 Nm 1.5 Nm
	General data
Operating position	optional
Storage temperature	-40 °C 70 °C
Ambient temperature	-25 °C 50 °C
Housing type	distribution board housing
Installation type	Mounting rail (35 mm)
Housing material	thermoplastic
Protection class	IP40

sealable	true
Width	17.8 mm
Height	80 mm
Depth	72 mm
Installation depth	66 mm
Module widths	1
Weight	0.115 kg
Design requirements/Standards	EN 60898-1
Power limitation category	3
Degree of pollution	2

Dimensions



Dimensioned drawing miniature circuit-breakers ELS 3 B4o/1+N

Wiring example



Wiring example miniature circuit-breakers ELS $_3$ B4o/1+N