



symbolic image

## DATA SHEET

### residual current operated circuit-breakers with integral overcurrent protection

#### RCBO 1 C32/0,03/1-AC

#### sensitive to residual currents Type AC

Article number 09915837



#### Function

RCCB/MCB combinations (RCBO) are residual current operated circuit-breakers with integral overcurrent protection for protecting systems in the event of a short-circuit and overload as per the requirements of VDE 0100 Part 430, and for protecting persons, farm animals and material items in the event of earth leakage currents as per VDE 0100 Part 410. Overload tripping occurs at currents in the overload range through a short-time delayed, heat-sensitive bimetal trip and at short-circuit currents through an electromagnetic instantaneous trip. The high-quality residual current operated circuit-breakers with integral overcurrent protection from series RCBO 1 are independent of the mains voltage and have a high switching capacity of 10 kA. They are especially suited for use in British standard distribution systems, and are particularly compact thanks to a module width of just one module width unit. Two features make mounting and removal easier: terminal protection against wires being lodged behind them and the bi-stable snap-in slider. Switches with residual current characteristic AC only detect AC residual currents. They cannot detect pulsating DC residual currents so are not permitted for use as residual current operated protective devices in Germany. They are therefore only available as export models. RCBOs with tripping characteristic C are primarily suitable for power circuits with high switch-on or peak currents, as their short-circuit trip value is five to ten times the rated current. Devices of this series have been designed in accordance with the requirements of the British Standards Institution. Due to their voltage dependence, they are not admitted for use in Germany.

#### Features

mains-voltage-dependent tripping, compact design for all rated currents, high short-circuit resistance, green/red switching position indicator, strain-relief clamps with protection against wires being lodged behind them, bi-stable snap-in slider for easy mounting and removal

#### Mounting

quick fastening to mounting rail, any installation position, supply as desired

#### Applications

Power supplies to residential and purpose-built buildings as well as industrial facilities with TN-S, TT and TN-C-S networks. In IT networks, the RCBOs of this series can be set to switch off in the event of a second fault, Not permitted for use in TN-C networks and for protecting systems in which electronic equipment may cause pulsating or smooth DC residual currents or residual currents with frequencies not equal to 50 Hz. Comprehensive protection is not provided with an RCCB type AC. For these applications we recommend our residual current operated circuit-breakers with integral overcurrent protection Type A or our AC-DC sensitive RCBO Type B.

#### Technical Data


| Technical Data                               | RCBO 1 C32/0,03/1-AC |
|--|----------------------|
| Series                                       | RCBO 1               |
| Number of poles                              | 1                    |
| Residual current type                        | AC                   |
| Rated current (AC)                           | 32 A                 |
| Rated residual current IΔn                   | 0.03 A               |
| Short-time delayed                           | false                |
| Selective                                    | false                |
| min. Operating voltage range of test circuit | 184 V                |
| max. Operating voltage range of test circuit | 264 V                |

Subject to technical changes

| Technical Data  | RCBO 1 C32/0,03/1-AC                                  |
|---|---|
| Tripping characteristic                                 | C   |
| Operating voltage (AC)                                  | max. 253 V  |
|   | <b>load circuit</b>                                   |
| Specification   | load disconnect contact                               |
| Rated voltage (AC)                                      | 230 V   |
| Rated current (AC)                                      | 32 A  |
| Rated short-circuit current                             | 10 kA   |
| Surge current strength                                  | 0.25 kA   |
| max. Total rated switching capacity                     | 10 kA   |
| Rated frequency   | 50 Hz   |
| Current heat loss per current path                      | 10.7 W  |
| Short-circuit backup-fuse SCPD                          | 100 A   |
| Back-up fuse type                                       | gG  |
|   | <b>screw-type terminal top, bottom (load circuit)</b> |
| Neutral conductor position                              | right   |
| Clamping area   | 1 mm <sup>2</sup> ... 25 mm <sup>2</sup>              |
| Connection C1 Maximum number of conductors per terminal | 2 (conductors of same type and cross-section)         |
|   | <b>General data</b>                                   |
| Operating position                                      | optional  |
| Mechanical endurance                                    | min. 20000 switching cycles                           |
| Electrical endurance                                    | min. 4000 switching cycles                            |
| Storage temperature                                     | -25 °C ... 55 °C                                      |
| Ambient temperature                                     | -25 °C ... 40 °C                                      |
| Climate resistance                                      | according to IEC 60068-2 (90...95%)                   |
| Housing type  | distribution board housing                            |
| Installation type                                       | Mounting rail (35 mm)                                 |
| Housing material  | thermoplastic   |
| Protection class  | IP20 (installed: IP40)                                |
| Width   | 17.7 mm   |
| Height  | 102.6 mm  |
| Depth   | 75.2 mm   |
| Installation depth                                      | 70.2 mm   |
| Module widths   | 1   |
| Weight  | 0.195 kg  |
| Design requirements/Standards                           | EN 61009-1, EN 61009-2-1, EN 61543                    |
| Power limitation category                               | 3   |


Subject to technical changes

## Dimensions



Dimensional drawing Group view

## Wiring example



Wiring diagram