



symbolic image

DATA SHEET

auxiliary switches

DHi 7

for displaying the operating status

Article number 09917988



Function

Auxiliary switches report the status of the main devices to which they are fitted. Auxiliary switches DHi 3 to DHi 8 can be retro-fitted to miniature circuit-breakers from series DLS 6 h, hsl or i. The auxiliary switch activates in parallel to the DLS 6 miniature circuit-breaker when switched off by hand or because of overload or short-circuit. Other indicators (buzzers, indicator light, etc.) can be used to display the operating status of a miniature circuit-breaker.

Features

auxiliary switch function for DLS 6, different contact designs available, compact design (0.5 module width units), complies with IEC 60947-5-1, EN 60947-5-1 and VDE 0660-200

Mounting

mounting by clamping to the right of the basic device , quick fastening to mounting rail, any installation position

Applications

These devices are suitable for querying the operating status of power supplies to residential and purpose-built buildings as well as to industrial facilities.

Notes

The auxiliary switch does not affect the function of the basic device.


Technical Data

Technical Data	DHi 7
Series	DHi 7
suitable for model range	DLS 6
Mounting side	right
Number of (n.o, n.c.,change-over)	0 0 1
	load circuit
Specification	switching contact
Rated voltage (AC)	230 V
Rated current (AC)	max. 4.8 A
Rated power	min. 0.1 VA
Allowed utilization category	AC-15, DC-13
max. Rated current AC-15 120 V	9.6 A
max. Rated current AC-15 230 V	4.8 A
max. Rated current DC-13 125 V	3.5 A
max. Rated current DC-13 250 V	1.8 A
	screw-type terminal top and bottom (load circuit)
Allowed types of wires	solid conductor, flexible conductor, stranded conductors with ferrule
Cross section solid	1-wire: 0.5 mm ² ... 2.5 mm ²
Connecting capacity flexible	1-wire: 0.5 mm ² ... 1.5 mm ²
Cross section flexible with ferrule	0.5 mm ² ... 1.5 mm ²
	General data

Subject to technical changes

Technical Data	DHi 7
Duty cycle	continuous operation (Duty cycle \leq 100 %, at Ue)
Operating position	optional
Housing type	distribution board housing
Installation type	Mounting rail (35 mm), Device extension
Protection class	IP20 (installed: IP40)
Width	8.8 mm
Height	87 mm
Depth	68.3 mm
Installation depth	72.8 mm
Module widths	0.5
Weight	0.046 kg
Design requirements/Standards	EN 60947-5-1, VDE 0660-200

Dimensions



Dimensional drawing Group view

Wiring example



Wiring diagram