



DATA SHEET
input terminals
AS 25-Si
 for busbars for Eurovario series
 Article number 09920087



Function

Terminals for busbars to supply switching devices. Series AS terminals allow the supply to MCBs (one-pole+N).


Features

for 1-pole+N MCBs, load capacity up to 80 A, Eurovario system

Technical Data

| Technical Data | AS 25-Si |
|---------------------------------------|--|
| Series | AS 25-Si |
| Accessories design | input terminal |
| Number of terminal connections | 1 |
| Rated voltage (AC) | max. 690 V |
| screw-type terminal (supply) | |
| Allowed types of wires | solid conductor, stranded conductors with ferrule, flexible conductors without ferrule, most flexible conductors without ferrule |
| Cross section solid | 1-wire: 6 mm ² ... 25 mm ² |
| Cross section flexible with ferrule | 4 mm ² ... 16 mm ² |
| Cross section stranded | 1-wire: 6 mm ² ... 25 mm ² |
| Cross section AWG, solid | 9 ... 4 |
| Tightening torque | max. 2 Nm |
| flange (connecting the device) | |
| General data | |
| Installation type | screw |
| Housing material | polyamide 66 (PA 66) |
| Protection class | IP20 |
| Width | 13 mm |
| Height | 14 mm |
| Depth | 31 mm |
| Weight | 0.01 kg |
| Design requirements/Standards | EN 60664-1 |

Dimensions



Dimensional drawing Group view

Subject to technical changes