

## DATA SHEET

Article number : 09945122



sensitive to pulsating and alternating currents Type A, characteristic C





#### **Function**

RCCB/MCB combinations (RCBO) are residual current operated circuit-breakers with integral overcurrent protection for protecting systems in the event of a short-circuit and overload as per the requirements of VDE 0100 Part 430, and for protecting persons, farm animals and material items in the event of earth leakage currents as per VDE 0100 Part 410. Overload tripping occurs at currents in the overload range through a short-time delayed, heat-sensitive bimetal trip and at short-circuit currents through an electromagnetic instantaneous trip. The DRCBO 4 have a rated switching capacity of 6 kA. They provide a labelling area in addition to the tripping indicator. Type A residual current circuit-breakers are sensitive to pulsating and alternating currents. This function is independent of the mains voltage. RCBOs with tripping characteristic C are primarily suitable for power circuits with high switch-on or peak currents, as their short-circuit trip value is five to ten times the rated current. Devices in standard design are intended for monitoring circuits with a rated voltage of 230 V or 400 V and a rated frequency of 50 Hz.

#### Features

pulsating current-sensitive and AC current-sensitive, mains-voltage-independent tripping, compact design for all rated currents, switch position indicator, separate indication of tripping cause, strain-relief clamps with a wide terminal cross-section range on both connection sides, neutral conductor right, labelling area

#### Mounting

quick fastening to mounting rail, any installation position, supply as desired

#### Applications

Protection of circuits in residential and purpose-built buildings as well as industrial facilities with TN-S, TT and TN-C-S networks. In IT networks, the RCCB/MCBs can be set to switch off in the event of a second earth fault, Not permitted for use in systems with TN-C networks; not permitted for protecting circuits in which the power electronics equipment may cause smooth DC residual currents or residual currents with frequencies not equal to 50/60 Hz.

### Accessories

auxiliary switches DRCBO 4 Hi 2, wiring components RCCB and MCB busbars 4-pole


### Technical data

Series	DRCBO 4
Number of poles	3+N
Residual current type	A
Rated current (AC)	10 A
Rated residual current I∆n	o.o3 A
Short-time delayed	false
Selective	false
min. Operating voltage range of test circuit	170 V
max. Operating voltage range of test circuit	250 V
Tripping characteristic	С
Operating voltage (AC)	max. 440 V
	load circuit
Specification	load disconnect contact
Rated voltage (AC)	230 V, 400 V
Rated current (AC)	10 A
Rated short-circuit current	6 kA
Surge current strength	0.25 kA
max. Total rated switching capacity	6 kA
Rated insulation voltage	440 V

Technical changes reserved 2025\_10\_25 doepke\_09945122\_dbl\_en.pdf 1/2


Rated impulse withstand voltage	4 kV
Rated frequency	50 Hz, 60 Hz
Current heat loss per current path	1.4 W
Back-up fuse type	gG
Overvoltage class	
	screw-type terminal top, bottom (load circuit)
Neutral conductor position	right
Connection C1 Maximum number of	2 (conductors of same type and cross-section)
conductors per terminal	
Cross section solid	1-wire: 1 mm <sup>2</sup> 35 mm <sup>2</sup> ; 2-wire: 1 mm <sup>2</sup> 10 mm <sup>2</sup>
Connecting capacity flexible	1-wire: 1 mm <sup>2</sup> 25 mm <sup>2</sup> ; 2-wire: 1 mm <sup>2</sup> 10 mm <sup>2</sup>
Cross section stranded	1-wire: 1 mm <sup>2</sup> 25 mm <sup>2</sup> ; 2-wire: 1 mm <sup>2</sup> 10 mm <sup>2</sup>
Tightening torque	2 Nm 2.4 Nm
	General data
Operating position	optional
Electrical endurance	min. 2000 switching cycles
Storage temperature	-40 °C 70 °C
Ambient temperature	-25 °C 40 °C
Housing type	distribution board housing
Installation type	Mounting rail (35 mm)
Housing material	thermoplastic
Protection class	IP20 (installed: IP40)
Width	70 mm
Height	92 mm
Depth	74 mm
Installation depth	68 mm
Module widths	4
Weight	0.503 kg
Design requirements/Standards	EN 61009-1, EN 61009-2-1, VDE 0664-20
Power limitation category	3
Degree of pollution	2

### **Dimensions**



 $Dimensioned\ drawing\ residual\ current\ operated\ circuit-breakers\ with\ integral\ overcurrent\ protection\ DRCBO\ 4\ C10/o,o3/3N-A$ 

# Wiring example



Wiring example residual current operated circuit-breakers with integral overcurrent protection DRCBO 4 C10/o,03/3N-A

Technical changes reserved 2025\_10\_25 doepke\_09945122\_dbl\_en.pdf 2 / 2