

DATA SHEET
Article number : 09980380

fuse-switch-disconnector
Tytan II Do-50-1/S
With fuse plug, without fuse



1/2



Function

Fuse-switch-disconnectors combine the fuse protection of system parts with switching capability under load as well as when in overload. Tytan II series devices are main fuse switch-disconnectors for Do1 and Do2 fuses. Simultaneous isolation of all phases is ensured by the screwcap-less plug-in technology. In contrast to the earlier screwcap technology, in which perfect contact could not be guaranteed, the mechanics of the series prevent the formation of high transitional resistances and therefore minimise thermal dissipation power. Disconnectors of this design are equipped with fuse plugs and colour-coded fitted cartridges according to the rated current.

Feature

low current heat losses, suitable for fuses Do1 and Do2, finger and back-of-hand proof, large clamping area

Mounting

quick fastening to mounting rail, Einbaulage aufrecht auf der Tragschiene

Applications

The components are suitable for use in power supplies to residential and purpose-built buildings as well as industrial facilities.

Notes

All variants are supplied without fuses. These can be obtained separately.

Accessories


fuse plug sets DSE, restart locks Tytan WES, wiring components Do busbar can be cut to length, input terminals DK

Technical data

Series	Tytan
Number of poles	1
Device type	plug-type technology without screw caps, similar to NH technology
Suitable for fuses	Do1: 1 A*, 2 A, 4 A, 6 A, 10 A, 13 A, 16 A (* – not standardised)
	Do2: 20 A, 25 A, 32 A, 35 A, 40 A, 50 A, 63 A
	load circuit
Specification	switching contact
Rated voltage (AC)	400 V
Rated voltage (DC)	max. 110 V
Rated current (AC)	50 A
Rated short-circuit current	50 kA
Rated insulation voltage	690 V
Rated impulse withstand voltage	6 kV
Allowed utilization category	AC-22b, DC-21b
Overvoltage class	IV
	screw-type terminal top, bottom (load circuit)
Protection against direct contact	finger and back-of-hand proof
Cross section solid	1-wire: 1.5 mm ² 35 mm ²
Connecting capacity flexible	1-wire: 1.5 mm ² 35 mm ² ; 2-wire: 1.5 mm ² 16 mm ²
Cross section flexible with ferrule	6 mm² 35 mm²
Cross section stranded	1-wire: 1.5 mm ² 35 mm ²
Tightening torque	max. 3 Nm
	Do2 (fuse mounting)
	General data
Electrical endurance	min. 1500 switching cycles

Storage temperature	-40 °C 70 °C
Ambient temperature	-25 °C 40 °C
Housing type	distribution board housing
Installation type	Mounting rail (35 mm)
Housing material	thermoplastic
Protection class	IP2oC (behind front panel with inserted fuse plugs)
sealable	true
Width	27 mm
Height	86 mm
Depth	70 mm
Module widths	1.5
Weight	0.123 kg
Design requirements/Standards	EN 60947-3
Fire class/creep resistance	Vo, glow wire test 960° / CTI 600
Degree of pollution	3

Dimensions



Dimensioned drawing fuse-switch-disconnector Tytan II Do-50-1/S

Wiring example



Wiring example fuse-switch-disconnector Tytan II Do-50-1/S