



**DATA SHEET**  
**doorbell transformers**  
**RK 24**  
**short-circuit-proof thanks to PTC**  
**Article number 09980654**



**Function**

Bell transformers generate one or more output voltages for the operation of doorbell systems, such as bells, buzzers or gongs. Transformers for converting mains voltage of 230 V to safety extra-low voltage.

**Features**

short-circuit-proof thanks to PTC, certified as per EN 61558, certified by VDE and KEMA, with ENEC approval mark for use in all Europe

**Mounting**

quick fastening to mounting rail, any installation position

**Applications**

Bell transformers in series RK are used for the AC power supply to bell systems, lock systems and relay circuits, for example.

**Notes**

Restore operation after a short-circuit by briefly disconnecting the primary power input, With small loads, or idling, the output voltage may rise, Only for transient loading, In the case of permanent loads we recommend using safety transformers.

**Accessories**


mounting kits RK

**Technical Data**

Technical Data		RK 24
Series		RK 24
Operating voltage (AC)		230 V
Operating frequency		50 Hz
Internal consumption		max. 11 W
		<b>load circuit</b>
Rated voltage		8 V/2 A (AC), 12 V/1.3 A (AC), 24 V/0.6 A (AC)
Rated voltage (AC)		8 V, 12 V, 24 V
Rated current (AC)		2 A, 1.3 A, 0.6 A
Rated power		max. 16 VA
Rated frequency		50 Hz
Type overload protection thermal		PTC, primary side
		<b>screw terminals with strain-relief clamp top and bottom</b>
Connection C1 Maximum number of conductors per terminal		2
Cross section solid		1-wire: 1.5 mm <sup>2</sup> ... 4 mm <sup>2</sup> ; 2-wire: 1.5 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>
		<b>General data</b>
Duty cycle		short-time operation (Duty cycle ≤ 1 min bei Nennlast, 5 min at max. 20 % of the nominal load)
Operating position		optional
Housing type		distribution board housing, wall-mounted housing
Installation type		Mounting rail (35 mm), Wall mounting


Technical Data	RK 24
Housing material	polycarbonate (PC)
Protection class	IP20
Width	36 mm
Height	90 mm
Depth	65 mm
Installation depth	60 mm
Module widths	2
Weight	0.396 kg
Design requirements/Standards	EN 61558-1

Dimensions



Dimensional drawing Group view

Wiring example



Wiring diagram