

installation relays RI 024-100 compact relays for switching high currents Article number 09981003



Function

Installation relays are monostable, i.e. they close the main circuit as long as there is control voltage. Thanks to different control voltages and contact configurations they are suitable for many applications, especially for switching lighting, boilers, etc. The series RI installation relays are suitable for switching single-phase consumers up to 20 A. They have the option of manual operation, a clearly detectable switch position indicator and a compact design even with high rated currents and powerful terminals. Thanks to the wide range of coil voltages and contact configurations, they can be used for many switching and control applications.

Features

high flexibility thanks to different contact configurations, Manual operation for test purposes, low switching noise and no humming or buzzing, front switch position indicator through manual operation key, Option of visual display of operating status via LED, Switching contacts with safe isolation AC1 as per EN 60947-4-1, Duty cycle: 100 % with spacer 0,5 mod, easy connection thanks to generously dimensioned, captive terminals, connection wires cannot become lodged behind the terminals, easy accessibility for connecting coil supply, Use of flame-resistant materials as chlorine-free and halogen-free plastics, Protected against direct contact under BGV A3

Mounting

quick fastening to mounting rail, any installation position with a tilt angle of max. 30°

Applications

The components offer universal use for control tasks in industrial and building systems as well as in domestic installations. They are especially suitable for switching lighting systems, electric heaters, fans, air conditioning systems, ventilators, heat pumps and glow and gas-discharge lamps.

Notes

The designation for the devices in the RI series includes the rated voltage (first group of digits) and the contact design (final group of digits), which is listed in the following order: normally opened contact, normally closed contact and changeover contact. A "RI 024-110" therefore has a rated voltage of 24 V, one normally opened contact and one normally closed contact, but no changeover contact, The duty cycle is max. 1 h. To reach 100 % duty cycle, the DHDS spacer must be used on both sides.

Accessories

spacers DHDS


Technical Data

Technical Data	RI 024-100
Series	RI 024
Number of (n.o, n.c.,change- over)	1 0 0
Operating voltage (AC)	24 V (21.6 V 26.4 V)
Operating frequency	50 Hz
Internal consumption	3.5 W 11 W
	Display status output
Number	1
Туре	operating button (black)
	control input
Galvanically separated	true
rated voltage (AC)	24 V

Technical Data	RI 024-100
Tolerance of rated voltage	-15 % 10 %
rated impulse withstand voltage	2 kV
Rated power	3.5 VA 11 VA
Rated frequency	50 Hz
min. Pulse duration control input	50 ms
Rated power (switch on)	10 VA 13 VA
rated power (retaining)	3.4 VA 4 VA
Tated power (retaining)	
Constitution	load circuit
Specification	relays
min. Contact opening	5 mm
Bounce time load circuit	typ. < 5 ms (max. 10 ms)
Rated voltage (AC)	250 V
Tolerance of rated voltage	-10 % 10 %
max. Rated current added	20 Å
max. Rated current not added	20 Å
Rated insulation voltage	500 V
Rated impulse withstand voltage	4 kV
Rated frequency	50 Hz
Allowed utilization category	AC-1, AC-3, AC-5a, AC-5b, AC-7a
Current heat loss per current	2 W
max. Rated current thermal	
	20 A
thermal Backup-fuse OCPD	20 Å
short-circuit backup-fuse SCPD	20 Å
Rated voltage AC-1 (fix)	250 V
max. Rated current AC-1	20 Å
max. rated switching capacity AC-1	30 A
max. Rated power AC-1	5000 VA
Rated voltage AC-3 3-phase (fix)	250 V
max. Rated current AC-3	8 A
max. rated switching capacity AC-3	64 A
max. Rated power AC-3	2000 VA
Rated voltage AC-5a (fix)	250 V
max. Rated current AC-5a	10 A
max. Capacity AC-5a	30 A
max. Rated power AC-5a	2500 VA
Rated voltage AC-5b (fix)	230 V
max. Rated current AC-5b	8.8 A
max. Capacity AC-5b	13.2 A
max. Rated power AC-5b	2024 VA
Rated voltage AC-7a (fix)	250 V
max. Rated current AC-7a	20 A
max. rated switching capacity AC-7a	30 A
max. Rated power AC-7a	5000 VA
max. rated power glow lamps	1980 VA
max. Rated power low-voltage	900 VA
halogen lamp	-


lamp compensated max. Rated power fluorescent lamp not compensated max. rated power fluorescent lamps duo-switching Iff terminal, captive top and bottom (load circuit, control input)	Technical Data	RI 024-100
max. Rated power fluorescent lamp not compensated max. rated power fluorescent lamps duo-switching lift terminal, captive top and bottom (load circuit, control input) Allowed types of wires copper conductor, stranded conductors with ferrule copper conducting spacing flexible section solid 1-wire: 0.5 mm² 10 mm²	max. Rated power fluorescent	1105 VA
lamp not compensated max. rated power fluorescent lamps duo-switching lift terminal, captive top and bottom (load circuit, control input) Allowed types of wires Copper conductor, stranded conductors with ferrule		
Intervention of the second sec		1020 VA
Ilift terminal, captive top and bottom (load circuit, control input) Allowed types of wires Copper conductor, stranded conductors with ferrule		
lift terminal, captive top and bottom (load circuit, control input) Allowed types of wires Copper conductor, stranded conductors with ferrule Cross section solid 1-wire: 0.5 mm² 10 mm² Connecting capacity flexible 1-wire: 0.5 mm² 10 mm² Cross section flexible with ferrule 0.5 mm² 6 mm² Cross section stranded 1-wire: 0.5 mm² 10 mm² Cross section stranded Duty cycle Short-time operation (Duty cycle ≤ 1 h, 100 % with spacer 0,5 mod. widths) Operating noise Operating noise Operating position not suspended, tilt angle 30° Mechanical endurance min. 1 · 106 switching cycles Electrical endurance min. 40000 switching cycles Housing type distribution board housing Installation type Mounting rail (35 mm) Housing material polycarbonate (PC) Protection class IP20 Width 18 mm Height 90 mm Depth 65 mm Installation depth Module widths 1		1700 VA
Allowed types of wires Cross section solid 1-wire: 0.5 mm² 10 mm² Connecting capacity flexible 1-wire: 0.5 mm² 10 mm² Cross section flexible with ferrule 0.5 mm² 10 mm² Cross section stranded 1-wire: 0.5 mm² Cross section stranded 1-wire: 0	lamps duo-switching	
Cross section solid 1-wire: 0.5 mm² 10 mm² Connecting capacity flexible 1-wire: 0.5 mm² 10 mm² Cross section flexible with ferrule 0.5 mm² 6 mm² Cross section stranded 1-wire: 0.5 mm² 10 mm² General data Duty cycle short-time operation (Duty cycle ≤ 1 h, 100 % with spacer 0,5 mod. widths) Operating noise no humming or buzzing, little switching noise Operating position not suspended, tilt angle 30° Mechanical endurance min. 4 noos switching cycles Electrical endurance min. 4 ooos switching cycles Ambient temperature -20 °C 45 °C Housing type distribution board housing Installation type Mounting rail (35 mm) Housing material polycarbonate (PC) Protection class IP20 Width 18 mm Height 90 mm Depth 65 mm Installation depth 60 mm Module widths 1		lift terminal, captive top and bottom (load circuit, control input)
Connecting capacity flexible 1-wire: 0.5 mm² 10 mm² Cross section flexible with ferrule 0.5 mm² 10 mm² Cross section stranded 1-wire: 0.5 mm² Cross section stranded 1-wire	Allowed types of wires	copper conductor, stranded conductors with ferrule
Cross section flexible with ferrule O.5 mm² 6 mm² Cross section stranded 1-wire: o.5 mm² 10 mm² General data Duty cycle Short-time operation (Duty cycle ≤ 1 h, 100 % with spacer o,5 mod. widths) Operating noise Operating position not suspended, tilt angle 30° Mechanical endurance Inin. 1 · 106 switching cycles Electrical endurance min. 40000 switching cycles Electrical endurance Ambient temperature -20 °C 45 °C Housing type distribution board housing Installation type Mounting rail (35 mm) Housing material polycarbonate (PC) Protection class IP20 Width 18 mm Height 90 mm Depth 65 mm Installation depth 60 mm Module widths	Cross section solid	1-wire: 0.5 mm ² 10 mm ²
General data Duty cycle short-time operation (Duty cycle ≤ 1 h, 100 % with spacer 0,5 mod. widths) Operating noise no humming or buzzing, little switching noise Operating position not suspended, tilt angle 30° Mechanical endurance min. 1 · 10° switching cycles Electrical endurance min. 40000 switching cycles Electrical endurance min. 40000 switching cycles Ambient temperature -20 °C 45 °C Housing type distribution board housing Installation type Mounting rail (35 mm) Housing material polycarbonate (PC) Protection class IP20 Width 18 mm Height 90 mm Depth 65 mm Installation depth 60 mm Module widths 1	Connecting capacity flexible	1-wire: 0.5 mm ² 10 mm ²
General data Duty cycle short-time operation (Duty cycle ≤ 1 h, 100 % with spacer 0,5 mod. widths) Operating noise no humming or buzzing, little switching noise Operating position not suspended, tilt angle 30° Mechanical endurance min. 1 · 10° switching cycles Electrical endurance min. 40000 switching cycles Ambient temperature -20 °C 45 °C Housing type distribution board housing Installation type Mounting rail (35 mm) Housing material polycarbonate (PC) Protection class IP20 Width 18 mm Height 90 mm Depth 65 mm Installation depth 60 mm Module widths 1	Cross section flexible with ferrule	o.5 mm² 6 mm²
Duty cycle short-time operation (Duty cycle ≤ 1 h, 100 % with spacer 0,5 mod. widths) Operating noise no humming or buzzing, little switching noise Operating position not suspended, tilt angle 30° Mechanical endurance min. 1 · 10° switching cycles Electrical endurance min. 40000 switching cycles Ambient temperature -20 °C 45 °C Housing type distribution board housing Installation type Mounting rail (35 mm) Housing material polycarbonate (PC) Protection class IP20 Width 18 mm Height 90 mm Depth 65 mm Installation depth 60 mm Module widths 1	Cross section stranded	1-wire: 0.5 mm ² 10 mm ²
Operating noise Operating position Operating position Mechanical endurance Electrical endurance Min. 1 · 106 switching cycles Electrical endurance Min. 40000 switching cycles Mobient temperature -20 °C 45 °C Housing type Installation type Mounting rail (35 mm) Housing material Polycarbonate (PC) Protection class IP20 Width 18 mm Height 90 mm Depth 65 mm Installation depth Module widths		General data
Operating position not suspended, tilt angle 30° Mechanical endurance min. 1 · 10° switching cycles Electrical endurance min. 40000 switching cycles Ambient temperature -20°C 45°C Housing type distribution board housing Installation type Mounting rail (35 mm) Housing material polycarbonate (PC) Protection class IP20 Width 18 mm Height 90 mm Depth 65 mm Installation depth 60 mm Module widths 1	Duty cycle	short-time operation (Duty cycle ≤ 1 h, 100 % with spacer 0,5 mod. widths)
Mechanical endurancemin. 1 · 106 switching cyclesElectrical endurancemin. 40000 switching cyclesAmbient temperature-20 °C 45 °CHousing typedistribution board housingInstallation typeMounting rail (35 mm)Housing materialpolycarbonate (PC)Protection classIP20Width18 mmHeight90 mmDepth65 mmInstallation depth60 mmModule widths1	Operating noise	no humming or buzzing, little switching noise
Electrical endurance min. 40000 switching cycles Ambient temperature -20 °C 45 °C Housing type distribution board housing Installation type Mounting rail (35 mm) Housing material polycarbonate (PC) Protection class IP20 Width 18 mm Height 90 mm Depth 65 mm Installation depth 60 mm Module widths 1	Operating position	not suspended, tilt angle 30°
Ambient temperature -20 °C 45 °C Housing type Installation type Mounting rail (35 mm) Housing material polycarbonate (PC) Protection class IP20 Width 18 mm Height 90 mm Depth 65 mm Installation depth Module widths 1	Mechanical endurance	min. 1 · 106 switching cycles
Housing type distribution board housing Installation type Mounting rail (35 mm) Housing material polycarbonate (PC) Protection class IP20 Width 18 mm Height 90 mm Depth 65 mm Installation depth 60 mm Module widths 1	Electrical endurance	
Installation type Mounting rail (35 mm) Housing material polycarbonate (PC) Protection class IP20 Width 18 mm Height 90 mm Depth 65 mm Installation depth 60 mm Module widths 1	Ambient temperature	-20 °C 45 °C
Housing material polycarbonate (PC) Protection class IP20 Width 18 mm Height 90 mm Depth 65 mm Installation depth 60 mm Module widths 1	Housing type	distribution board housing
Protection class IP20 Width 18 mm Height 90 mm Depth 65 mm Installation depth 60 mm Module widths 1	Installation type	Mounting rail (35 mm)
Width 18 mm Height 90 mm Depth 65 mm Installation depth 60 mm Module widths 1	Housing material	polycarbonate (PC)
Height 90 mm Depth 65 mm Installation depth 60 mm Module widths 1	Protection class	IP20
Depth 65 mm Installation depth 60 mm Module widths 1	Width	18 mm
Installation depth 60 mm Module widths 1	Height	90 mm
Module widths 1	Depth	65 mm
	Installation depth	60 mm
Design requirements/Standards EN 60947-1, EN 60715	Module widths	1
	Design requirements/Standards	EN 60947-1, EN 60715

Dimensions



Wiring example

Wiring diagram



Dimensional drawing Group view